MORBARK® 30 CHIPARVESTOR®



BENEFITS

- The largest in the line, the Morbark Model 30 Chiparvestor is designed for power! This aggressive machine features a chipper disc that is 5" thick and weighs 8,000 lbs., making it perfect for the toughest of jobs.
- With an 83" disc and a four-wheel hydraulic feed wheel compression system, this machine is fully equipped to handle what you give it.
- Customizable options include a three-, four- or six-knife chipper disc, electronic RPM sensor, tri-axle, reversing fan, track option and many more, making it ideal for any of your needs.
- Like all Morbark equipment, the 30 Chiparvestor is a long-lasting, durable machine backed by a world-class parts and service support team.



Chipper Disc

Each disc is fabricated from plate steel and put through ultrasonic testing. Material certification is issued for each disc, which provides the best chipper disc in the industry.



Feed System

Powerful multi-wheel feed system provides positive feed of logs and tops for excellent chip quality.



Operator's Cab (RXL) Roomy, climate-controlled cabs are equipped with comfortable seats, joystick controls and full instrumentation.



Chip Quality Units produce quality chips even in non-merchantable and juvenile timber.

SPECIFICATIONS

General

Length
Height 13'6" RXL/13'4" NCL
Width 11' RXL/10'4" NCL
Gross weight (RXL) 82,000 lbs.
Gross weight (NCL) 58,000 lbs.
Horsepower (RXL)up to 1050 HP
Horsepower (NCL) up to 875 HP
Engine CAT or Cummins
Tandem axle trailer 50,000 lb. suspension
Fuel capacity (tank) (RXL) 400 gallons
Fuel capacity (tank) (NCL) 300 gallons
Hydraulic oil capacity (RXL)
Hydraulic oil capacity (NCL) 200 gallons

Discharge System

Dirt separator with deflector Hydraulic swivel/telescoping discharge spout

Chipper

30" diameter chipping capacity83" diameter x 5" thick three-knife chipper disc with LH rotation

Knives (3): 23" x 5" x 1/2"

Chip sizes: 5/8", 3/4", 7/8", 1", 1-1/4", 2"

Hydraulic chipper hood for easy knife access

Feed System

30" x 10[°] CAT chain infeed bed (RXL) Three-wheel hydraulic feed system (RXL) Two 13" x 25-3/4" side feed wheels and one 22-1/4" x 68" top feed wheel

Four-wheel hydraulic feed system (NCL)

Remote Control

Wireless remote control with tethered back-up

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS 2/1/

Cab and Loader (WCL)

Enclosed weatherized operator's cab is mounted on rubber shock absorbers and tilts hydraulically for transport

Combination air conditioner/heater

Six-way adjustable seat and joystick controls

Morbark 1000 knuckleboom loader, 25' reach, 210° swing and by-pass grapple

Lift capacity of 20,000 lbs. at 10'

Options

Reversing fan Choice of PT Tech or Twin Disc hydraulic clutch or Twin Disc dry clutch Four-knife chipper disc Electronic RPM sensor Espar heating system for cold weather start Electric power



800.831.0042 989.866.2381 www.morbark.com PO Box 1000 8507 S. Winn Rd. Winn, MI 48896