Dynapac CP2100W

Pneumatic rollers





Technical data

Masses	
Operating mass (incl. ROPS)	20,900 lbs
Mass with max. ballast	46,300 lbs
Mass with wet sand ballast	31,200 lbs

Propulsion	
Speed low	5.6 mph
Speed high	14.0 mph

Compaction	
Rolling width	89 in
Tire overlap	1.7 in
Wheel loads, without ballast	3,000 lbs
Wheel loads, with wet sand ballast	4,450 lbs
Wheel loads, with max. ballast	6,600 lbs
Tire pressure, min	36 psi
Tire pressure, max	123 psi
Tire type (smooth)	14/70 R20
Water spray system, type	Pressurized
Water spray system, tank capacity	110 gal
Water spray system, spray nozzle	one per tire
Ballast volume	78 cu. ft.

Engine	
Manufacturer/Model	Cummins QSB 3.8 (Tier 4F)
Rated power, SAE J1995	118 hp @ 2,200 rpm
Туре	Water cooled turbo diesel
Fuel tank capacity	55 gal
Electrical system	24V

Engine	
Manufacturer/Model	Cummins QSB 3.8 (Tier 4F)
Rated power, SAE J1995	97 kW @ 2,200 rpm

Hydraulic system	
Driving	Axial piston pump with variable displacement. Axial piston motors (2) with variable displacement.
Steering	Axial piston pump with variable displacement.
Service brake	2 multidisc brakes on rear wheels activated by pedal.
Parking/Emergency brake	Failsafe multidisc brakes in both gear boxes.

Dynapac CP2100W

Pneumatic rollers



Technical data



