48 volt AC system

Vehicles by Taylor-Dunn

- speed up to 18 mph
- range up to 40 miles
- 3,000 lb. load capacity

10,000 lb. tow capacity

COMFORT & PERFORMANCE UTILITY V CLE



Taylor-Dunn is proud to announce an addition to its line of ergonomic BIGFOOT electric vehicles. The new BIGFOOT XL is a utility vehicle with a larger operator's compartment, hill climbing gusto, speed up to 18 mph, and all-wheel hydraulic disc brakes.

Equipped with a 17 hp, 48 volt AC motor, GT drive, and rack and pinion steering, this electric utility vehicle will out-perform any other in its class.

Available customizations include deluxe cab, econo cab, fold-away seat, steel panel box, lockable cargo box, stake sides and aluminum drop-down sides.

For additional vehicle images, videos, information and custom modifications visit taylor-dunn.com.

VOLTAGE	48 volt		
SPEED	up to 18 mph up to 29 km/h		
RANGE	up to 40 mi up to 64 km		
LOAD CAPACITY	3000 lb	1361 kg	
BED SIZE (W x L)	54 x 77 in	137 x 196 cm	
TURNING RADIUS	145 in	n 368 cm	

Based on Standard Configuration Typical Capacity: Actual load capacity depends on application and vehicle configuration.

FEATURES & BENEFITS:

- Zero Emissions
- XL Operator's Compartment
- Tilted Steering
- Adjustable Seats
- Exceptional Handling

















Dual USB Port

Adjustable Seats

Clear View Display

Recessed Tie-downs

LED Lighting

Tilted Steering

Anaheim, CA 92804

www.taylor-dunn.com contact@taylor-dunn.com Toll Free (800) 688-8680





ommercial and Industrial Vehicles Since 1949

Large Compartment

2114 West Ball Road

(714) 956-4040 Fax: (714) 956-3130

			Le.	77 in	
-BIGFOOT	ХОГ 💻			(196 cm)	
PERFORMANCE		ER	57.4 in		
	3,000 lb	1061 kg	(146 cm) w/ cab	• 54 in (137 cm)	
	,	1361 kg			
MAX SPEED (UNLOADED)	18 mph	29 km/h			
TURNING RADIUS	145 in	368 cm	9 in (3	34.5 in 42 cm)	
TOW CAPACITY	10,000 lb	4536 kg			
DIMENSIONS					
OVERALL LENGTH	130.5 in	332 cm			
OVERALL WIDTH	54 in	137 cm			
HEIGHT (- cab)	52 in		73 in 185 cm)		
HEIGHT (+ cab)	74 in	188 cm	51.5 in (131 cm)	27.5 in	
WHEEL BASE	62 in	158 cm	14.5 in (37 cm)	(70 cm)	
GROUND CLEARANCE	5.8 in	14.7 cm		62 in (157 cm) 12.5 in	
BED SIZE	54 x 77 in	137 x 196 cm		(32 cm) 331 cm)	
POWER SUPPLY / DRIVE TRAIN					
MOTOR	17 hp, 13 kW, AC				
SYSTEM VOLTAGE	48 Volt				
DRIVE AXLE	Helical Gear, Oil Bath Transaxle, GT Automotive Differential				
BATTERIES	260 Amp-hour, Lead Acid, 6 Volt, 8 Each				
CHARGER	Built-in, 48V, 115 VAC/60 Hz, 1kW w/ Interlock, 17 Amp SCR				
CONTROLLER	Solid State Self Diagnostic AC Speed Controller				
CHASSIS	The second second				
FRAME	Fully Welded, Unitized, 12 Gauge, Smooth Skin Steel Body				
STEERING	Rack and Pinion				
SUSPENSION	Multi-leaf Springs, Front & Rear GT Automotive Drive				
BRAKES	Hydraulic Disc Brakes, Front & Rear, Electric Parking Brake				
BUMPERS	Heavy Duty Steel Integrated Front & Rear				
TIRES	20.5 x 8 x 10, Load Range E, Pneumatic				
GENERAL					
UNIT WEIGHT	1965 lb	891 kg			
SEATS	Adjustable Black Bucket Seats, Driver's Seat Electrical Interlock, 2 Person				
INSTRUMENTATION	Clear View Display (Speed, Distance, Battery Status Indicator, Hours, Input Diagnostic & Fault Code Display), Dual USB Port, Emergency Power Cut-off Switch, Light Switch, Forward/Off/Reverse Selector, Reverse Alarm, High/Low Speed Selector, Key Switch, DC/DC Converter (on with key switch), and Electric Horn				
LIGHT ACCESSORIES	Dual LED Headlights, Taillights and Brake Lights				
CONFORMANCE	Type E OSHA 1910.1	Type E OSHA 1910.178, ANSI B56.8			
OPTIONS					
• FOLD-AWAY SEATS	ALUMINUM DF	ROP-DOWN SIDES	STEEL F	PANEL BOX	
STAKE SIDES	DELUXE CAB	W/ STEEL DOORS	• BATTER	Y WATERING SYSTEM	
ECONO CAB	DIAMOND PLA	ATE DECK	• VARIOU	S HITCHES	
			= = = =		

- PORTABLE CHARGER
- STROBE LIGHT
- VINYL DOORS
 - Specifications, standard equipment, accessories and modifications are subject to change without notice.

LOCKABLE CARGO BOX

• LIFT OUT BATTERY BOX

• DIRECTIONAL SIGNALS

• UNDERCOATING

GALVANIZED FRAME

• OPTIONAL PAINT COLORS